



OVERVIEW

The Safe-Pro Level IIIA Ballistic Blanket meets NIJ 0108.01 Level IIIA protection standards against NIJ 0108.01 IIIA projectiles and velocities and can provide protection against shrapnel caused by detonation of explosive devices. Ballistic blankets can be used for personal protection as well as be used to fortify windows, doors and walls.



SPECIFICATIONS

Model: SPVA-BRB-III A

Overall Size: 4' x 6' (48" x 72")

Protection Level: Compliant to NIJ Standard 0108.01 Level IIIA

Projectiles and Velocities: Fully meets NIJ 0108.01 Level IIIA, projectiles 9 mm and 44 magnum at the velocity of 1400 ft. / sec. +/- 50 ft. / sec.

This blanket can also be used as a blast and fragmentation resistant blanket.

Thickness: 0.5 Inch

Carrier (Outer Cover) Materials: Constructed of high tenacity, tough and abrasion resistant 1000 Cordura nylon fabric in black on one side and coyote on the opposite side. Flame resistant carriers are available as an option.

Weight: 30 lbs.

Warranty: 8 Years from Date of Sale on the ballistic insert

Custom Sizes, Designs and Colors Are Available

Functions:

- May be used in a vehicle for personal protection
- May be used in an Active Shooter situation
- May be used as a breacher blanket
- May be used to protect sensitive equipment from fragmentation, blast and ballistic threats
- Use as stretcher in First Response situations

MADE IN THE USA





OVERVIEW

Construction Details of the Level IIIA Ballistic Blanket:

Model: SPVA-BRB-III A

Overall Size: 4' x 6'(48" x 72")

Protection Level: Compliant to NIJ Standard 0108.01 Level IIIA.

1. The size 4 ft x 6 ft blanket has 10 handles.
2. Each handle is constructed of 2" heavy duty nylon webbing straps, each strap cut to 18" length, 2 pieces which are then stitched together, leaving 3.5" unstitched ends.
3. The handle is positioned to be 6 inches from the end of the blanket.
4. The length between the stitched ends of each handle is 6 inches.
5. The two webbing straps which are sewn together to stitch the handle, are attached on both sides of the blanket (see photo).
6. Ten of these handles are sewn on the blanket, two each on the 4 feet side and three each on the 6 feet side.
7. The label is sewn 13 inches from the raw edge of the blanket.
8. 2 inch perimeter stitch is sewn around the entire periphery of the blanket.
9. Additional stitches are sewn through the ballistic pad at a distance of 15 inches from the perimeter stitch in the width direction and 12 inches from the perimeter stitch in the length direction of the blanket.
10. Each handle is stitched to the nylon Cordura outer cover with a 2" Box section with an "X" stitch.

MADE IN THE USA

